

irri5



Irri5 is a battery-operated irrigation programmer with two-wire “latch” electric valves.

It has a screen and three keys which are used for configuration, consultation, programming and manual activation.

CHARACTERISTICS

The main characteristics of the unit are:

- Outputs for 5 sectors or 4 sectors and 1 fertilizer (plus a general output in both cases).
- Two inputs for malfunction and conditional stop.
- Capacity for 5 programs with 5 possible sequential irrigation sectors in each.
- Several programs can be activated at the same time.
- Every program has 3 daily start times and activation frequency in days.
- Manual start up and stopping of programs and sectors.
- One 9 volt battery power supply.
- Low battery indicator (it needs to be replaced).
- Power supply options:
 - Power supply with three 9 volt batteries.
 - 12 Vdc power supply.

CONSULTATION AND PROGRAMMING

The sections of consultation, programming, change clock time, manual working of programs and manual working of sectors can be accessed from the main menu. The values displayed in these sections go with an identifying code.

The “+” and “-” keys are used to modify the values displayed on the screen. These keys increase or decrease the value displayed on the screen in that moment. If the key is pressed for more than two seconds the value increases or decreases faster.

Use the “C” key to access a section from the main menu, or to move to the next value when we are already in one of the sections.

WARRANTY

Agrónic 4000 is compliant with all the norms defined by the CE.

The products created by Progrés enjoy a 2 year warranty against all manufacturing defects.

SISTEMES ELECTRÒNICS
PROGRÉS, S.A.

Avda. Urgell,23 - 25250 BELLPUIG (Lleida) España

Tel. (+34) 973 32 04 29 - Fax (+34) 973 33 72 97

info@progres.es

www.progres.es